



A LEGACY BUILT ON SAFETY & TRUST

Founded by Shri O.P. Jindal in 1970, Jindal Stainless is one of the largest stainless steel conglomerates in India and ranks amongst the top 10 stainless steel conglomerates in the world. Jindal Stainless Group has an annual crude steel capacity of 2.9 MTPA and an annual turnover of \$ 4.2 Billion USD (as on Mar'2023).

Our growth has been backed by the excellence of our people, value driven business operations, customer centricity, adoption of one of the best safety practices in the stainless steel industry and a commitment for social responsibility.








ABOUTSTAINLESS STEEL

Stainless steel is the common name for all steel grades containing at least 10.5% chromium. chromium improves the corrosion resistance of stainless steels. In addition to iron and chromium, stainless steels contain other alloying metals, of which the most important are nickel and molybdenum. The combination of chromium and oxygen leads to the formation of a chromium-rich passive layer on the surface of the steel. This layer protects the steel, and re-forms over time if damaged.


On the basis of their microstructure, Stainless steels are divided into Austenetic, Ferritic, Duplex and Martenesitic types. More than 100 different stainless steel grades have been developed for various applications.

The alloying metals influence the corrosion resistance, durability, strength and formability of the steel.





C M Y K







DESIGN FLEXIBILITY

CARBON STEEL

The section type and structural configuration are influenced by the corrosion mitigation, thereby limiting the choices available to the designer while optimising the design.

STAINLESS STEEL

In view of superior corrosion resistance, the structural engineer is free to select the most aesthetic and economical structural configuration with closed sections and any other combination, purely based on strength and serviceability parameters.



JINDAL INFINITY INFRA SOLUTIONS FOR STRUCTURAL APPLICATIONS

A. Plates

i. Thickness - 3 mm - 80 mmii. Width - 1500 mm maxiii. Length - 12000 mm max




B. Fabricated Girders

- i. JSL offers welded stainless-steel
 I-beams, H-beams, hollow-section
 tubes and bent profiles for
 load-bearing structures.
- ii. These products are available in lengths of up to 12 m without length splicing.
- iii. As per the approved drawing.


C. Angles & Channels

Cold Rolled formed / press sections



JINDAL INFINITY PROPERTIES

Upto 186x better corrosion resistance



Corrosion performance as per SAE J2334 test consists of alternating wet/dry cycles with salt for 8 weeks, leads to low maintenance.

Mechanical Properties

Grade	Yield Strength	Tensile Strength	% Elongation	Impact
IRS 350 CR	350 MPA min	485 MPA min	18 min	34 J min
IRS 450 CR	450 MPA min	585 MPA min	18 min	27 J min

Physical Properties	Values
Density (kg/m3)	7750
Modulus of Elasticity (N/mm2)	2 x 10 ⁶
Poisson's Ratio	0.3
Thermal Conductivity (W/mK)	24.6
Mean Coefficient of Thermal Expansion /°C	10.4 x 10 ⁻⁶

Chemical Composition


Jindal Infinity confirms to ASTM A1010 and RDSO specification BS-S-7.5.3.1-9

Element	C	Mn	Si	S	Р	Ni	Мо	Cr	N	Other
Min. %							0.10-	10.5-		
Max.%	0.03	1.5		0.01	0.04	1.5	0.75	12.5	0.03	

^{*}Maximum, unless range or minimum is indicated


Fatigue Strength

C M Y ■ K



Fatigue behavior ASTMA709 Grade 50CR steel in comparison to the other conventional structural steels (1 ksi = 6.9 MPa).

Courtesy: W. Shi and B. Phares.



Percentage of drop in the moment capacity as a function of age

RECOMMENDED FASTENERS DETAILS FOR FABRICATION OF JINDAL INFINITY

ltem	Code	Grade
Bolt	ASTM A193	GR B8 Class 2
Nut	ASTM A194	GR 8
Washer		Type 303

All types of nuts & bolts domestically available.

Visit **www.makestainless.com** for suppliers of consumables, fasteners and fabricated components.

Weldability of Jindal Infinity

It is recommended to use ER308L, ER309L, ER316L, and their higher silicon content counterparts, however ER309L has by far been the most widely used filler wire for welding of the plate girders fabricated with Jindal Infinity. Suitable flux should be used with filler wires. For FCAW, ER 309L and for GMAW – ER 309L/ER 309LMo with Gas mixture Ar-98% are recommended. However, any other suitable welding consumable permissible by AWS D1.6 may also be used.

LCC Analysis:

- A. Initial cost increase is 20-25% over existing carbon steel.
- B. Low maintenance over carbon steel. For aesthetics purpose, paint is recommended for utility Ferritic stainless steel. Addresses the current challenges of maintaining bridges like safety, accessability, shutdowns, additional cost for upkeeping and channelizing dedicated resources for the repeated jobs.
- C. Weight reduction of more than 25-30% achieved due to higher yield strength and light weight design.
- D. Payback period is less than 20 years.
- E. Stainless steel is green material and helps in reducing carbon foot print.
- F. Service life of stainless steel is more than 100 years.

STANDARDS AND CODES


Standard	Corresponding Design Code	Corresponding Construction / Fabrication Code
EN 10088 (Part 1 – List of stainless steel) (Part 2 – TDC for sheets/plates and strips of corrosion resisting steels for general purposes) (Part3-TDC for semi-finished products, bars, rods, wire, sections & bright products of corrosion resisting steels for general purposes) (Part4-TDC for sheet/plate and strip of corrosion resisting steels for construction purposes)	EN 1993-1-1(General Design Rules),EN 1993-2 (Steel Bridges) & EN 1993-1-4 (Supplementary Rules for Stainless Steel	EN 1090-2: Execution of steel structures (Technical Requirements for Steel Structures)
ASTM A1010/A1010M (standard specification for higher-strength martensitic stainless steel plate, sheet, and strip ASTM A709/A709M (standard specification for structural steel for bridges) ASTM 240 (standard specification for chromium and chromium-nickel stainless steel plate, sheet, and strip for pressure vessels and for general applications	AASTHO LRFD Bridge Design Specifications	AASTHO LRFD Bridge Construction Specifications
BS-S-7.5.3.1-9 (Specification for higher-strength martensitic stainless steel for bridge and associated structural applications IRS 350 CR)	AASTHO LRFD Bridge Design Specifications	AASTHO LRFD Bridge Construction Specifications

Jindal Infinity confirms to ASTM A1010 and RDSO specification BS-S-7.5.3.1-9 $\,$









1.10mm

27mm

Thickness (t)

STAINLESS STEEL CHEQUERED PLATES

PATTERNED ALONG THE BEST **GLOBAL STANDARDS**


The pattern of this Stainless Steel Chequered Plate is in accordance with IS 3502 Pattern 1A.

Dimensions of Bead*



LOWER LIFECYCLE COST FOR A LIFETIME OF GROWTH

LCC OF SS 409M HRAP CHEQUERED VS MILD STEEL HF CHEQUERED OVER 30 YEARS LIFE




Supplying of anti-skid chequered plates for gangway, trolly refuge, man refuge, side pathway, etc. shall be confirming to latest IS 6911, ISS Symbol 409 M, Minimum 6mm thick (excluding bead height) with flat bottom and top pattern confirming to IS 3502, 1A For, coastal/corrosive areas, thickness may be suitably increased depending upon severity of corrosion.

Appropriate matching stainless steel grade fasteners as recommended by manufacturer shall be used.

C M Y K

UP TO 5 TIMES HIGHER WEAR RESISTANCE FOR HIGHER COST SAVINGS

Grade 409M is known for its high wear resistance. Under the sliding wear test condition grade 409M is 1.6 times better than HSLA steel and 4.7 times better than normal mild steel.



INNOVATED FOR A STRONG & LONG-LASTING FUTURE

PRODUCT RANGE





Width Upto 1500mm



THE PROMISE OF PROGRESS

STRENGTHENED BY SAFETY AND RELIABILITY

Railway Bridge Pathway: Ensuring safety & convenience during maintenance and inspections.





JINDAL STAINLESS CHEQUERED SHEETS

Architectural Stairs & Flooring with a lustrous finish and high aesthetic appeal.





Chemical Composition of SS Rebar Grade G (410 L) as per IS 16651:2017:

Chemical	С	Ni	Mn	Si	Р	S	Cr	N
Min %							11	
Max %	0.03	0.6	1	1	0.04	0.03	13.5	-

Mechanical Properties of High Strength Deformed Stainless Steel Bars and Wires as per IS 16651:2017:

S. No.	Properties	SS 500	SS 550	SS 600	SS 650
1	0.2 percent proof stress (Rp0.2), Min, N/mm2	500	550	600	650
2	Percentage elongation after fracture (A5), Min, on gauge length 5.65 VA, where A is the cross-sectional area of the test piece	16	14.5	10	10

Product Offering:

Diameter (mm)	8 mm to 32 mm
Standard Length	12 mtrs.


Policy from Ministry of Road Transport and Highways:

Use of stainless steel in bridges on National Highways and other centrally sponsored projects to be constructed in marine environment susceptible to severe corrosion.

Policy No. RW/NH-34049/03/2020-S&R (B)







Grade:	EN 1.4404	EN 304	EN 204CU	EN 430	EN 316L
Width:	300mm	Thickness	1.2mm	Length	300mm









^{*}Load test certified by Govt. approved laboratory conforming to IEC 61537









BHAYANDAR RAILWAY STATION, MUMBAI DIVISION, WESTERN RAILWAY

Project Details

Project Bhayandar FOB, Western

Contractor Sai Projects Mumbai Pvt Ltd., Mumbai

Fabricator Sai Projects Mumbai Pvt Ltd., Mumba

Stainless Steel Supplier Jindal Stainless Ltd.

Stainless Steel used in Project

Product Application Quantity (MT) Grade HRAP plates/sheets (6mm to 40mm thickness) Girders / columns/ hollow sections IRS350CR

STAINLESS STEEL FOOT OVER BRIDGE

SRIKAKULAM ROAD RAILWAY STATION, WALTAIR DIVISION, EAST COAST RAILWAY

Project Details

Project

Srikakulam FOB, Waltair Division, East Coast Railway

Contractor

MD Jahageer, Visakhapatnan

Fabricator


Pennar Industries Ltd. Hyderabad


Stainless Steel Supplier


Jindal Stainless Ltd

Stainless Steel used in Project

Grade	Product	Application	Quantity (MT)
IRS350CR	HRAP plates/sheets (6mm to 40mm thickness)	Girders / ccolumns/ hollow sections	142
X2CrNi12	HRAP chequered sheets (3.5mm & 4mm thickness)	Roof deck sheet	18
X2CrNi12	CRAP sheets (2mm thickness)	Walkway side protective sheeting	5







RAILWAY BOARD CIRCULARS NOTIFICATIONS - SS FOB AND ROB

ELILLE

S. N. 81

Rajeev Verma राजीत वर्मा Executive Director/B&S कार्यकारी निदेशक / पुल एवं संरचना



भारत बारकार — रेल मंत्रालय अनुसंभात अभिकल्य और गानक सगडन लंशनक — 226011 Government of India Ministry of Railways Research Designs & Standards Organisation Lucknow 226011 Rly: 032-47120 Phone Fas 0522-2450398 Email: edbardso@gmail.com

No. CBS/FOB

EDCE/B&S Railway Board Rail Bhawan New Delhi. Dated: 01/07/2019

Sub: Stainless steel for structural application.

Ref: (i) Railway Board letter no. 2012/CE-II/BR/Presentation dated 10/05/2019.
(ii) Priorities initiatives for financial year 2019-20 issued vide CRB Note No. 2019/E&R 10/10/7 dated 30/04/2019.

In reference to subject matter, Indian stainless steel development association made a presentation in Railway Board on 13/05/2019. The presentation was attended by Railway Board officials including PED/Bridges, EDCE/B&S/Railway Board, ED/B&S/RDSO, Director/CE-I& II/B&S, Railway Board, CBE/Northern Railway and officials from Northern Railway.

The key point noted from the presentation are as under:

- 1. The stainless steel is advantageous over the carbon steel and it is being used in many of the bridges all over the world due to its higher yield strength, corrosion resistance property and aesthetic appeal. It is an ideal material for bridges in high chloride exposures i.e. coastal areas as compared to carbon steel as the carbon steel has a high corrosion rate. In such conditions, stainless steel provides sufficient corrosion protection with lower maintenance during its design life.
- 2. The main advantages are;
 - Resistance to Corrosion leads to very low maintenance.
 - (ii) Strength & Durability.
 - (iii) Sustainable-helps in reducing carbon foot print.
 - (iv) Though the initial cost increase is 20-25% over existing carbon steel, however, saving over service life of 60 years is 40%.
 - (v) Weight reduction due to higher yield strength leading to light weight design.

It was concluded by PED/Bridges that Indian Railways can go for field trial for FOBs manufactured using stainless steel. Further, Vide ref (ii) above, i.e. Priorities 30.04.2019, the possibility of use of stainless steel girder (FOB) in corrosion prone area is also to be examined.

In view of above, it is proposed that field trials may be ordered for four FOBs of stainless steel on Central Railway, Southern Railway, South Eastern Railway and East Coast Railway.

Railway Board is requested to consider the matter suitably.

(Rajeev Verma)
Executive Director/B&S

6/

C M Y K

Emailed on date.

Rajeev Verma राजीव वर्मा Executive Director/B&S कार्यकारी निदेशक / पुल एवं संरचना



भारत सरकार - रेल मंत्रालय अनुसंधान अभिकल्प और मानक संगठन लखनऊ - 226011 Government of India-Ministry of Railways Research Designs & Standards Organisation Lucknow-226011 Rly,: 032-42120 Phone / Fax; 0522-2450398 Email: edbs/rdso@gmail.com

No. CBS/Stainless Steel FOB

Dated: 04/07/2019

EDCE/B&S Railway Board Rail Bhawan New Delhi.

Sub: Stainless steel for structural application.

Ref: This office letter no. CBS/FOB dated 01/07/2019.

In continuation to this office letter above, the following additional information is

The design of stainless steel FOBs shall be done by Zonal Railways through reputed consultants and got proof checked from IITs. Thereafter, the duly proof checked design and drawings should be sent to RDSO for clearance. The design basis is attached at Annexure — I which has already been given to Western Railway vide this office letter dated 27/06/19. The general configuration of FOBs should be as per the RDSO standard drawing of FOB. drawing of FOB.

DA: As above.

04/7/14 (Rajeev Verma)

GOVERNMENT OF INDIA MINISTRY OF RAILWAYS (RAILWAY BOARD)

No. 2017/50/CE-III/BR/FOB

New Delhi, dt : 09.07.2019

Principal Chief Engineers CR. ECOR. NR. SR. SER & WR.

Instruction No.23/2019

Sub: Stainless Steel for Structural Application Ref: i) RDSO's letter no. CBS/FOB dt. 01.07.19 ii) RDSO's letter no. CBS/Stainless Steel FOB dt. 04.07.19

RDSO, vide letters referred (i) & (ii) above, proposed that Stainless Steel girder for FOB in corrosion prone area is useful and provide sufficient corrosion protection with lower maintenance. With a view to use of Modern Construction Techniques for longer life of structures, the following

- (a) Use of Stainless Steel will be carried out in CR, ECoR, NR, SR and SER for FOBs. In addition, WR is already using the same in one FOB.
- (b) Each zone will select two FOBs one FOB by Open Line and one by Construction Organization preferably (Targeted to be completed during 2019-20). CBE of the Zonal Railways will decide the FOBs depending upon the corrosion proneness of the area and will ensure that Stainless Steel girder issued for FOBs at most corrosive part of concerned Zonal Railways.
- (c) Design of Stainless Steel FOBs shall be done by the Zonal Railways through reputed consultants and got proof checked from IITs. RDSO will finally approve the design.
- (d) RDSO will be actively associated in the above and will provide all assistance to the Zonal Railways concerned with design
- (e) The above may be executed, by the concerned Zonal Railways, out of the available sanctions (of works) for the current Financial Year.

This item is in the list of priority initiative of Railway Board. Therefore, it should be completed at the earliest and monthly progress should be submitted to Board regularly.

This issues with the approval of Board (ME).

artia (O. N. Sharma)
Director Civil Engineering/ B&S
Railway Board Email: dcebsrb@gmail.com

Copy, for information and necessary action to:

- 1. CAO/Cs. CR. ECoR. NR. SR. SER & WR
- 2. CBEs/ CR, ECoR, NR, SR, SER & WR 3. ED/B&S, RDSO, Lucknow

Instructions No. 31/2019

GOVERNMENT OF INDIA MINISTRY OF RAILWAYS (RAILWAY BOARD)

No.2017/50/CE-HI/BR/FOB

New Delhi Dt: 04.11.2019

Principal Chief Engineers Central Railway, Mumbai Western Railway, Mumbai

Sub: Stainless Steel for Structural Application.
Ref: (i) This office of even letter no. dated 09.07.2019.
(ii) ED/B&S/RDSO's letter no. CBS/Stainless Steel/FOB dt. 30.08.2019, 03.09.2019 & 22.10.2019.

30.08.2019, 03.09.2019 & 22.10.2019.

Vide this officer letter referred (i) above, use of stainless steel for construction of POB was permitted in some of the Zonal Railways including CR & WR. Further, RDSO vide letters referred (ii) above, proposed that stainless steel for ROBs in corrosion prone area is useful and provide sufficient corrosion protection with lower maintenance. With a view to use of Modern Construction Techniques for longer life of structures, following have been decided:

(a) Use of stainless steel will be carried out in CR & WR for ROBs.

(b) Both the Railways will select one ROB of each design such as plate girder composite type with concrete deck on top, through girder type (truss type) and new design of multi cell box girder (pre-fabricated).

(c) CBE of the Zonal Railways will decide the ROBs depending upon the corrosion proneness of the area and will ensure that stainless steel for ROBs are used at most corrosive part of concerned Zonal Railways.

(d) Design of Stainless steel ROBs shall be done by the Zonal Railways through reputed consultants and got proof checked from IITs. RDSO will finally approve the design.

- reputed consultants and got proapprove the design.

 (e) Fabrication & inspection of these girders (ROBs) shall be governed as per
 Railways Board letter no. 2016/54/CE-III/BR/RDSO/Misc, dated
- 15.07.2019.

 (R) RDSO will be actively associated in the above and will provide all assistance to Zonal Railways concerned with design (as in 'd' above).

 (g) The above may be executed, by the concerned Zonal Railways, out of the available sanctions (of works).

 Zonal Railways are advised to take action at the earliest and monthly progress should be submitted to Board regularly.

This issues with the approval of Board(ME).

(O. N. Sharma)

Director Civil Engineering/B&S Railway Board

Email: dcebsrb@gmail.com

Copy, for information and necessary action to: 1. CAO/Cs, CR & WR 2. CBEs, CR & WR

- 3. ED/B&S,RDSO, Lucknow

GOVERNMENT OF INDIA MINISTRY OF RAILWAYS (RAILWAY BOARD)

No.2017/50/CE-III/BR/FOB

New Delhi, Date: 30.07.2020

Director General. Manak Nagar, Lucknow

Sub: Stainless Steel for Structural Application.

Ref: (i) Board's letter No. 2017/50/CE-III/BR/FOB dated 09.07.2019 (ii) Minutes and Recommendations of PCEs Seminar issued by Director IRICEN letter No. 151/20307 dated 25.06.2020

In PCEs conference held on 19^{th} and 20^{th} June-2020 the issue of development of specification and standard drawings for various standard span configuration of stainless steel FOB was decided as under:

"FOB constructed using stainless steel structural members are aesthetically beautiful and having more resistance of corrosion. Hence, it is proposed to execute all new FOBs, duly adopting stainless steel structural members. Specifications and drawings for various standard span configurations need to be issued for execution of FOB, using stainless steel structural members."

In view of above, RDSO is requested to issue specifications and standard drawings for various configurations in next 3 months, which will be used by zonal railways in corrosion prone areas. Progress made in this regard should be submitted to Board every month.

> 30/7/2020 (O. N. Sharma) Dir. CE/B&S

Copy to:
Principal Chief Engineer/All Zonal Railways - for information.
ED(B&S)Steel/RDSO - for necessary action.

C M Y K

RAILWAY BOARD - SS REBAR

GOVERNMENT OF INDIA MINISTRY OF RAILWAYS RAILWAY BOARD

No. 2018/06/CE-III/BR/Stainless Steel

New Delhi, dt. 02.05.18

Principal Chief Engineers, All Zonal Railways.

Chief Administrative Officers (Construction) All Zonal Railways.

209

Sub: Use of Stainless steel reinforcement in various structures.

Ref:
i) Board's letter no. 2016/4/CE-III/BR/BSC/84 Seminar dt. 28.07.17
ii) Board's letter no. 2017/51/CE-III/BR/CRB dt. 03.11.17
III) A&C slip – 6 dt. 27.07.17of IRS Concrete Bridge Code

Vide reference above, instructions have been issued that stainless steel reinforcement conforming to IS 16651:2017 may be used in corrosion prone structures to prevent corrosion and ensure overall durability of structure. In continuation of same, a committee of SAG level officers was constituted by Board for specifying the corrosion prone structures where stainless steel reinforcement can be used and to also deliberate on cost implications. A copy of the committee's report is enclosed herewith.

2.0 Based on the recommendations of the aforesaid committee, Board (ME) has decided that Stainless steel reinforcement bars (Grade G (410L)- Ferritic conforming to IS 16651:2017) to be used for the following structures:

- Bridges in coastal area (up to 30 kms from coast): Railway bridges, FOB, ROB/RUB, Rail Flyover/Metro, Mono Rail crossings.
- · Tunnels in coastal areas.
- C & W and Loco inspection pits, catwalks, washing aprons & water tanks at all places.
- Any other structure located in extremely adverse environmental conditions or where frequent inspection is not possible even if it is away from coastal area after due justification & with the personal approval of PCE.

The necessary action may be taken accordingly under intimation to Board.

DA: As Above

(V.K.Jain)
Director CE/B&S
Railway Board

copy for information and necessary action to:

- Director General/RDSO
- 2. CMD/RVNL, IRCON, RITES, New Delhi
- 3. CMD/KRCL, MRVC, Mumbai
- 4. ED/MTP, Railway Board

MINISTRY OF ROAD TRANSPORTATION & **HIGHWAY - SS REBAR**



RW/NH-34049/03/2020-S&R (B) **GOVERNMENT OF INDIA** MINISTRY OF ROAD TRANSPORT & HIGHWAYS

S&R - (Bridges) Transport Bhawan, 1, Parliament Street, New Delhi-110001

Dated: 22.01.2021

To,

1. The Chief Secretaries of all the State Governments / UTs.

- 2. The Principal Secretaries / Secretaries of all States / UTs Public Works Department dealing with National Highways, other Centrally sponsored schemes
- 3. The Engineers-in-Chief and Chief Engineers of Public Works Department of States/UTs dealing with National Highways, other Centrally sponsored schemes.
- 4. The Director General (Border Roads), Seema Sadak Bhavan, Ring Road, Delhi 110010.
- 5. The Chairman, National Highways Authority of India, Plot G-5 & 6, Sector-10, Dwarka, New Delhi 110075.
- 6. The Managing Director, NHIDCL, PTI Building, Parliament Street, New Delhi 110001.

Sub: Use of Stainless Steel in Bridges on National Highways and other centrally sponsored Projects to be constructed in marine Environment Susceptible to Severe Corrosion.

Sir,

Ministry vide circular No RW/NH/34041/44/91-S&R dated 14th March, 2000 prescribed use of Fusion Bonded Epoxy Coated Reinforcement in Bridges on National Highways and other centrally sponsored Bridge Projects in Marine Environment as detailed thereto. The various specifications, conditions etc. for use of Fusion Bonded Epoxy Coated Reinforcement have also been stipulated in the above said circular.

- The instructions given hereby are now in supersession of the above circular in light of experience/knowledge gained and modifications/evolution of further standards/specifications.
- It has been decided that the stainless steel conforming to the requirement stipulated in IS:16651:2017 shall be used for reinforced concrete bridges (superstructure and substructure) on National Highways located in Extreme Environment Exposure as defined in IRC:112:2020. In locations, where it is difficult to ascertain the environment exposure condition, a zone within 15 km from the sea or creek shall be considered as Extreme Environment.
- The contents of this Circular may please be brought to the notice of all the Concerned in your Organization for strict implementation. This circular will be implemented from the date of its issuance.
- This issues with the approval of the Competent Authority.

Yours faithfully,

(Jitendra Kumar), Superintending Engineer, S&R - (Bridges), For Director General (Road Development) & SS.

Copy to:

- All Technical Officers in the Ministry of Road Transport & Highways. All Joint Secretaries in the Ministry of Road Transport & Highways. All ROs & ELOs of the Ministry of Road Transport & Highways.
- 3.
- The Secretary General, Indian Roads Congress.
- 5. The Director, IAHE, Noida
- Technical circular file of S&R (B) Section.
- NIC for uploading on Ministry's website under "what's new".

Copy for kind information to:

- PS to Hon'ble Minister (RT&H, MS&ME) / PS to Hon'ble MOS (RT&H).
- Sr. PPS to Secretary (RT&H).
- PPS to DG (RD) & SS
- PPS to AS & FA/ADG-I/ADG II/ ADG III/ ADG IV

****** End ******

26

ADOPTION OF PRINCIPLES OF LIFECYCLE COST (LCC) ANALYSIS

No.F.1/37/2018-PPD Government of India Ministry of Finance Department of Expenditure Procurement Policy Division

> 512, Lok Nayak Bhavan, New Delhi. Dated 2nd January, 2019

OFFICE MEMORANDUM

Subject :- Adoption of principles of Life Cycle Cost (LCC) Analysis.

Attention is invited to Rule 136(1)(iii) of GFR 2017 wherein it has been provided that no work shall be commenced or liability incurred in connection with it until a properly detailed design has been sanctioned; while designing the projects etc. principles of Life Cycle cost (LCC) may also be considered. It has been brought to the notice of this department by Ministry of Steel that the principles of LCC are not being adopted while preparing Detailed Project Report (DPR) or at the time of finalization of the tender terms. In this regard, it is again advised that provisions of GFR relating to LCC may be considered while designing the projects. Consulting engineers/ structural engineers/ metallurgists may be consulted wherever considered appropriate.

(K Narayana Reddy) Under Secretary to the Govt. of India Tel.: 24621305

Email: kn.reddy@gov.in

To,


Secretaries of All Central Government Ministries/ Departments



































C■M Y■K

EDGE AHEAD WITH THE JSL EDGE



Regular Supplier to Railways



Approved by RDSO



Wide Manufacturing Range



State of the Art Technology



Largest SS Manufacturer



Fully Integrated Plant



Socially Responsible Company



Flexibility: 50 MT Heat



Wide Marketing Network



Environment Friendly Company



Indian Railways' Most Trusted Fabrication Partner



Chain of Service Centres





NOTES





NOTES







Zone	Name	Contact	Email
	Shoaib Ahmed	7894457755	shoaib.ahmed@jindalstainless.com
East	Bahadur Goipai	8708787126	bahadur.goipai@jindalstainless.com
	Abhishek Raj	8873097234	abhishek.raj@jindalstainless.com

Zone	Name	Contact	Email
	Gaikwad Tanmay Sudam	7304304362	tanmay.gaikwad@jindalstainless.com
West	Tejas Jadhav	702135827	tejas.jadhav@jindalstainless.com

Zone	Name	Contact	Email
North	Manoj Bhutani	8826818981	manoj.bhutani@jindalstainless.com
	Kunj Gupta	8054228667	kunj.gupta@jindalstainless.com
	Ritik Bharti	9163492219	ritik.bharti@jindalstainless.com
	Sandeep Kumar	9560306222	sandeep@jindalsteelway.com

Zone	Name	Contact	Email
South	Kadithi Avish	9909947036	kadithi.avish@jindalstainless.com
	Bose Christy Arun	9566114629	bose.arun@jindalstainless.com

Segment	Name	Contact	Email
Industrial	Devender Devgun	8800699454	devender.devgun@jindalstainless.com
Structures	Gautam Pruthi	9971430400	gautam.pruthi@jindalstainless.com
	Bhanu Pratap Rao	9660009813	bhanup.rao@jindalstainless.com

Contact for Advisory
Mr. Nagarajan P.:- 8130757806
Contact for Sponsorship
Ms. Pranjali Singh:- 7488631417
pranjali.singh@jindalstainless.com

Email: infinity@jindalstainless.com www.jindalstainless.com



